Designed for clinical excellence

Hospital-grade performance to VET-PET practice.

MELLIFLUUS CORE 1

See more. Know more.

We care -introducing the mAAbbu PET VET- specific Intensive Care Hemodynamic Monitoring solution (MC-1) designed to significantly reduce risk + elevate patient safety through every precise intervention.



Temp



Pulse



ECG



SYS + Diastolic





REAL TIME FEATURES

- √ SP02 % measurement
- √ Electrocardiogram (ECG) measurement
- √ Patient / PET specific cuffs
- √ Pressure indicator for the 5x cuff sizes
- √ Patient Temperature measurement

- √ Systolic and diastolic Blood Pressure
- √ Fully Portable
- Pulse rate & indicator
- ✓ Pulse Waveform
- √ RESP (rpm) = Respiration Rate

Our purpose is to create **medical Awareness for all Alive beings beside us** (mAAbbu) - by producing unique outstanding products & solutions which fulfill market needs with the outcome of a better world.



Technical Data Sheet

m A b b u ™

MELLIFLUUS CORE 1

MC1 (MC1D1) with s	tarter accessories and consumables	Opt. accessories and consumables
TFT 2.9" Color L	CD (EN55011 Class A)	
Pressure with +/	/-3 mmHg max. deviation	
Systolic (SYS) 3	0mmHg -255mmHg (real time displayed)	
Mean arterial pr	essure (MAP) 20mmHG-235mmHg measuremen	į
Diastolic (DIA) 1	5mmHG-220mmHg (real time displayed)	
Temperature vas	scular/surface 25°C -45°C (real time displayed)	
Heart rate 15bpr	m to 300bpm (real time displayed)	
		MC1AA1
RESP (rpm) = Re	espiration Rate via ECG (real time displayed)	
Pulse Rate 40-240bpm with +/-2 bpm (real time displayed)		
Memory trend chart with memory		
Consumables	Single use animal specific cuff sizes (Latex fr	ee)
	· 1xXS pressure cuff (3 – 6cm)	MC1CSXS1
	· 1xS pressure cuff (4 - 8cm)	MC1CSS1
	· 1xM pressure cuff (6 - 11cm)	MC1CSM1 MC1CSL1
	· 1xL pressure cuff (7 - 13cm	MC1CSXL1
	· 1xXL pressure cuff (8 - 15cm)	
Accessories	Multi use animal specific cuff sizes (Latex fre	e)
	· 1x mid animal cuff 6-11cm*	MC1AR1M*
Function	Cuff Pressure Indicator	
Weight 256g ++-	+ Dimensions 140mmx82mmx46mm	
Battery 3.7v with	n 1800mAh lithium battery	
Wired DC 5.0V /	1A with battery level indicator	
Wireless charging dock 5W with battery level indicator MC1AC1		MC1AC1
1x USB-A to USE	1x USB-A to USB -C power cable MC1PC1	
Battery saver: after 90s non-activity sleeping mode with 2.5s wake up		
Visual battery level Indicator		
Operational temperature -5°C to 40°C with a maximum of 85% humanity		
Application indicators (visual movement disturbance indicator)		
Bluetooth Module		
bluetootti Modu		
	mobile carry case in black	MC1ACC1
		MC1ACC1 MC1ANIT1
1x MC1 specific	be cable	
1x MC1 specific 1x MC1 NIBP tul 1x User & Install	be cable	
	TFT 2.9" Color L Pressure with +/ Systolic (SYS) 3 Mean arterial pr Diastolic (DIA) 1 Temperature va: Heart rate 15bpt Electrocardiogra incl. VET specifi PET Oxygen satt in % incl. cables RESP (rpm) = Re Pulse Rate 40-2 Memory trend co Consumables Accessories Function Weight 256g ++- Battery 3.7v with Wired DC 5.0V / Wireless chargin 1x USB-A to USE Battery saver: af Visual battery le Operational tem Application indice	TFT 2.9" Color LCD (EN55011 Class A) Pressure with +/-3 mmHg max. deviation Systolic (SYS) 30mmHg -255mmHg (real time displayed) Mean arterial pressure (MAP) 20mmHG-235mmHg measurement Diastolic (DIA) 15mmHG-220mmHg (real time displayed) Temperature vascular/surface 25°C -45°C (real time displayed) Heart rate 15bpm to 300bpm (real time displayed) Electrocardiography ECG measurement (real time displayed) incl. VET specific alligator clips (clips MC1AA1) PET Oxygen saturation (SpO2 35%-100%, real time displayed) in % incl. cables and clips +++ Red & Infrared (666nm-905nm) RESP (rpm) = Respiration Rate via ECG (real time displayed) Pulse Rate 40-240bpm with +/-2 bpm (real time displayed) Memory trend chart with memory Consumables Single use animal specific cuff sizes (Latex from 1xXS pressure cuff (3 - 6cm) 1xS pressure cuff (6 - 11cm) 1xL pressure cuff (6 - 11cm) 1xL pressure cuff (7 - 13cm) 1xXL pressure cuff (8 - 15cm) Accessories Multi use animal specific cuff sizes (Latex from 1xXL pressure lndicator) Weight 256g +++ Dimensions 140mmx82mmx46mm Battery 3.7v with 1800mAh lithium battery Wired DC 5.0V /1A with battery level indicator 1x USB-A to USB -C power cable Battery saver: after 90s non-activity sleeping mode with 2.5s wake Visual battery level Indicator Operational temperature -5°C to 40°C with a maximum of 85% hur Application indicators (visual movement disturbance indicator)

*additional multi use cuffs available: MC1 Re-usable VET specific blood pressure cuffs XS to XL size

For the most up-to-date information, please consult the latest mAAbbu price list and/or catalogue. Article numbers, product specifications, and available accessories/consumables may have changed since the publication of this information. Please also refer to our current General Terms and Conditions.













Let's talk about what matters.

